





Key Spec

⇒ Efficacy: Up to 130 lm/w ⇒ LED Chip: SMD3030

⇒ SDCM: <5

⇒ **Beam Angle**: 70°x140° PC lens

⇒ IP Rating: IP65


⇒ Control (optional): None⇒ Installation: Ø60mm Pole

⇒ Warranty: 3 years

Application

Site, area, road and other lighting applications; Ideal for large retailers, commercial to medical properties, and big box retailers. And suitable for roadways.

Photometry



Product Data

Model No.	KML-SL050Z	KML-SL100Z	KML-SL150Z	KML-SL200Z	KML-SL240Z
Power	50W	100W	150W	200W	240W
Lumen Output	6,500 lm	13,000 lm	19,500 lm	26,000 lm	31,200 lm
Luminous Efficacy	130 lm/w				
ССТ	3000K 4000K 5000K 5700K 6500K				
CRI	Ra≥70 (Ra≥80 optional)				
Input Voltage	100 to 240 VAC/220 to 240 VAC; 50Hz/60HZ				
Spigot Size	Ø60mm				
Housing Color	Gray/Black				
Housing Material	Aluminum, PC				
Operating Temperature	-30°C to +40°C				
Operating Humidity	10% to 90% RH				
Lifespan	50,000 hours				
Warranty	3 years				


ErP Technical Specification


ltem	Specification/Data		
Efficiency In	>88%		
Power Factor	PF>0.90		
Standard Deviation of Color Matching	<5		
Lumen Maintenance at e.o.l.	>70%		
Lifetime	L70/B10@50,000hours		

Mounting & Accessories (optional)



Dimension (Non-adjustable mounting angle; unit: mm)





KML-SL200Z KML-SL240Z

Dimension (Adjustable mounting angle; unit: mm)

